



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: sales@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

13-Nov-2018

Product Number : 5152202TFT4

RoHS

Overall Shielded Cable 2/C 22/7 AWG Stranded Tinned Copper
SR-PVC Insulation
Overall Foil Shield & Overall Drain
PVC FT-4 Jacket
Operating Temperature: -20 to 105°C

General Specification of Product :

Final Diameter : 0.142 inches 3.607 mm

Total Cable Weight: 21 kg/km 14 lbs/1000 ft

Conductor : 22 AWG 7 Stranded Tinned Copper Conductor

Insulation : SR-PVC

Shield : Overall Foil Shield

Drain \ Ground: 24 AWG 7 Stranded Tinned Copper Conductor

Outer Jacket : PVC FT4

Outdoor Rating : Sunlight Resistant

Certification and Approvals : CSA AWG 600V 105°C CSA/UL CMG 300V 105°C

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C SUN RES LL61365 OR CSA AWM II A/B
105°C 600V FT4 (UL) CMG E132883 105°C #22 AWG ROHS

Electrical Characteristics :

DC Resistance 25°C: 15.8 Ohms / 1000 ft

Mutual Capacitance : 43.4 pF/ft

Cond to Shield Cap. : 81.5 pF/ft

Impedance : 55 Ohms

Velocity of Prop : 60 %

Inductance. : 1.3 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within +/- 10%)

5152202TFT4